

Analyze refrigerant purity and save your A/C machine

Contaminated refrigerant can damage your A/C machine, leading to expensive repairs



WHY?

Contaminated refrigerant **can damage your A/C machine**, leading to costly repairs. Impure refrigerant can contain leak-stoppers or other chemicals that can clog filters, coils, hoses and more within a machine.

Contaminated refrigerant **can also damage a customer's A/C system**, requiring costly replacement of system components and premature system failures.

Testing refrigerant purity before recovery can prevent those contaminants from ever touching your machine – **keeping your investment running as intended.**

Refrigerant analyzers are required for R-1234yf service and recommended prior to servicing R-134a systems to **protect your equipment.**

R-ID Plus

Features

- › Quickly and accurately determines refrigerant purity
- › Advanced ergonomic design
- › Displays % purity for R-1234yf, R-134a, and R-12
- › Displays % for R-22, unknown refrigerant, and hydrocarbons
- › Displays air % independent of the refrigerant sampled
- › Capable of analyzing R-12 (1/4" flare coupler sold separately)
- › Multiple languages: English (default), German, Spanish, French, Italian, Portuguese, Chinese, Japanese, Korean, and Russian
- › Easily prints test results with built-in printer
- › Uses Standard 57 mm thermal paper
- › Improved oil resistance with user replaceable hose assembly
- › Fender-compatible resting surface
- › Full color liquid crystal display (LCD) with on-screen instructions
- › Accelerated 70 second test time
- › Internal, rechargeable lithium-ion battery for cordless operation in any location
- › USB port for connection to the A/C service machine and remote software updates
- › All accessories stored in a hard-shell portable storage case



R-ID Plus: SP01957200

A/C machine maintenance

Get filters before the beginning of the season for preventative maintenance

- › Keep recovery and recycling units operating at peak efficiency with a convenient maintenance kit.
- › Contains one quick change filter-drier to be used on R-1234yf and R-134a stations, and one 600 ml bottle of our Premium High Vacuum Pump Oil.



Vacuum Pump Oil:

SP00100086

Filter-drier:

SP01100355

No bundle available in EU

Refrigerant leak detection

Tracer gas leak detection

LD3



LD5



LD7



LD9

